

## SPECIFICATIONS (UT33D)

Basic Functions	Range	Best Accuracy
DC Voltage	200mV/2000mV/20V/200V/500V	±(0.5%+2)
AC Voltage	200V/500V	±(1.2%+10)
DC Current	2000µA/20mA/200mA/10A	±(1%+2)
Resistance	200Ω/2000Ω/20kΩ/200kΩ/20MΩ/200MΩ	±(0.8%+2)
Special Functions		
Diode		✓
Continuity Buzzer		✓
Square Wave Output		✓
Data Hold		✓
Display Backlight		✓
Low Battery Display		✓
Input Impedance for DC Voltage Measurement	Around 10MΩ	✓
Max. Display	1999	✓

## GENERAL CHARACTERISTICS

Power	9V Battery (6F22)
LCD Size	48 x 16mm
Product Colour	Red and Grey
Product Net Weight	156g
Product Size	130 x 73.5 x 35mm
Standard Accessories	Test Lead, Battery, English Manual, Holster
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	60pcs
Standard Carton Measurement	490 x 356 x 315mm (Around 0.055 CBM Per Standard Carton)
Standard Carton Gross Weight	18kg

Specifications and other information are subject to change without further notice.

[Back to main menu](#)